DATA SHEET

LL3200T

All-round widescreen

Issue: June 2009

An attractive price doesn't mean that you have to compromise on style or performance. Thanks of latest panel technology the Display LL3200T saves up to 50% power consumption in operating mode.

HD resolution 1600 x 900 for excellent entertainment experience

Energy Star compliant: low typical power consumption and power management according to EPA

51 cm / 20-inch widescreen display in optimum 16:9 movie format

Fast response time (typ.) of 5 ms, perfect for Internet, home office, multitasking and more

50% reduction of power consumption
Due to integrated speakers no further accessories needed

LL3200T

Special features	
	Lifetime Extender, ECO control button, Aspect ratio conversion
Stand details	
Stand	removable
Tilt angle	-5° / +15°
Picture performance	
Contrast - advanced	10,000:1
Response time black to black typical	5 ms
Viewing angle (h/v)	170° / 170°
Color performance	16.7 Mio colors (Hi-FRC)
Brightness - typical	250 cd/m²
Size and resolution	
Aspect ratio	16:9
Diagonal Size	50.8 cm (20-inch)
Resolution (native)	1600 x 900 pixel (recommended)
Resolution (interpolated)	1440 x 900 pixel, 1366 x 768 pixel, 1280 x 1024 pixel
Picture size	443 x 249 mm
Pixel Pitch	0.277 mm
Frequencies	
Horizontal	30 - 82 kHz
Vertical	56 - 76 Hz
Frequencies - bandwidth	165 MHz
Connectivity	
Video input	1 x D-SUB
Audio sound output	2 x 1 W
Audio signal input	3.5 mm stereo phone jack
OSD Languages and setting options	
Languages	Czech, Danish, Dutch, English, Finish, French, German, Hungarian, Italian, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish, Turkish
Brightness / Contrast	Brightness, Contrast
Color	Cold, Warm, Custom Color
Image adjust	Clock, H-Position, V-Position, Expansion
Audio	Mute, Volume
Information	Resolution/mode, Signal input
Mode	General, Movie, Picture, Game
Power consumption (typical, w/o sound)	
Soft switch off	0.6 W
Power save mode	0.7 W
Operating with EPA settings	18 W
Operating maximum brightness	21 W
Electrical values	
Rated voltage range	100 - 240 V
Rated frequency range	50 - 60 Hz
Protection class	1
Compliance	
Europe	CE

Compliance	
USA/Canada	FCC Class B, cUL
Australia/New Zealand	C-Tick
Russia	GOST
Saudi Arabia	SASO
Global	ENERGY STAR® 4.1, ISO13406-2 (Pixel fault class II), IT-Eco-Declaration, RoHS, WEEE
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/default.aspx

Quality and Reliability	
MTBF (demonstrated)	70000 h

Dimensions / Weight / Environmental	
Dimension without stand (W x D x H)	472.8 x 56.4 x 297.4 mm
Dimension with stand (W x D x H)	472.8 x 214.9 x 377 mm
Weight (packed)	5.4 kg
Weight (unpacked)	4.1 kg
Weight (Monitor only)	
Operating ambient temperature	5 - 35°C

Miscellaneous	
	VESA DDC/ CI, Standardized mounting interface VESA FP MP MI 100 mm, Kensington lock

Package content	
	Data cable 1.8m, D-SUB (15-pin), Audio cable 1.8m, Power cable for wall socket (Euro-Schuko-Type CEE7) 1.8m, User manual, Warranty booklet, Quickstart flyer

Order information	
SAP order name	LL3200T
Order Code	S26361-K1316-V160
EAN-Nr.	4049699072505

Information about environmental care, policies, programs and our Environmental Guideline FSC 03230:
http://ts.fujitsu.com/aboutus
Take back and Recycling information:
http://ts.fujitsu.com/recycling

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded.
Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.
For further information see http://ts.fujitsu.com/terms_of_use.html
Copyright © Fujitsu Technology Solutions June 2009

Published by
Fujitsu Technology Solutions
http://ts.fujitsu.com